

REFERENCE: 74

Riverside Tool Corporation list of products used including MSDS sheets.

August 13, 2008. 7 pages



0001



Riverside
TOOL CORP.

**Profits Depend On
The Tools You Choose**

August 13, 2008

To: Mark Jaworski:
Fax: 317-234-0428
Total Pages: 6

Re: Your request for EPA.

Here is a list of the products and the machines they're used in.

GrindKlean by Eagle International – Used in small grinding machines.

Clearedge 6519 by Castrol Industrial Northern America, Inc. – Used in the machine shop lathe and milling machines.

Ionoplus 3000 by Oelheld GmbH – Used in a wire EDM machine.

Transogrind TG 250 by Transor Filter USA – Used in CNC grinders.

The first page of each MSDS will follow. I've also included a copy of an invoice from our waste removal service, Safety-Kleen Systems, Inc. Let me know if you need any more information.

Best Regards,

Kevin Koon
Plant Manager
Riverside Tool Corp
(574) 522-6798

From Kevin Koon w/ Riverside Tool

MATERIAL SAFETY DATA SHEET

TRANSOR FILTER USA

TRANSOGRIND TG-250

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFIER.....TRANSOGRIND TG 250
COMPANY'S NAME.....TRANSOR FILTER USA
COMPANY'S ADDRESS.....1285 OAKTON, ELK GROVE VILLAGE, IL 60007
COMPANY'S PHONE.....800-864-3040
DATE ISSUED.....SEPTEMBER 1, 1999
DATE REVISED.....AUGUST 10, 2000

SECTION 2. COMPOSITION AND INFORMATION ON INGREDIENTS

CAS NAME.....LUBRICATING OIL, HYDROCRACKED, HYDROTREATED AND HYDROISOMERIZED
CAS NUMBER.....84742-46-7 % (v.v) 100

SECTION 3. HAZARDOUS IDENTIFICATION

TOXIC AND HAZARDOUS INGREDIENTS.....NONE
HAZARDOUS DECOMPOSITION PRODUCTS.....CARBON MONOXIDE, CARBON DIOXIDE AND SULFUR OXIDES
FROM BURNING

SECTION 4. FIRST AID AND MEASURES

EYE CONTACT.....IMMEDIATELY FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES AND CALL
A PHYSICIAN.
SKIN CONTACT.....REMOVE EXCESS WITH CLOTH OR PAPER. WASH THOROUGHLY WITH SOAP AND WATER.
INHALATION.....REMOVE VICTIM TO FRESH AIR AND CALL A PHYSICIAN.
IF SWALLOWED.....CALL A PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING. (VOMITING MAY CAUSE ASPIRATION
INTO LUNGS RESULTING IN CHEMICAL PNEUMONIA.)

SECTION 5. FIRE-FIGHTING MEASURES

SPECIAL FIRE FIGHTING PROCEDURES.....DO NOT USE WATER EXCEPT AS FOG
UNUSUAL FIRE AND EXPLOSION HAZARDS.....NONE
FLASH POINT.....>275 F, ASTM D92, CLEVELAND OPEN CUP
FLAMMABLE LIMITS %.....N/A
EXTINGUISHING AGENTS.....DRY CHEMICAL, OR WATER FOG, OR CARBON DIOXIDE, OR FOAM
NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) - HAZARD IDENTIFICATION
HEALTH 1 FLAMMABILITY 2 REACTIVITY 0

SECTION 6. ACCIDENTAL RELEASE MEASURES

MATERIAL RELEASE OR SPILL.....TRANSFER BULK OF MIXTURE INTO ANOTHER CONTAINER. ABSORB RESIDUE
WITH AN INERT MATERIAL SUCH AS EARTH, SAND, OR VERMICULITE. SWEEP UP
AND DISPOSE AS SOLID WASTE IN ACCORDANCE WITH LOCAL, STATE, AND
FEDERAL REGULATIONS.

SECTION 7. HANDLING AND STORAGE

DO NOT HANDLE OR STORE AT TEMPERATURES OVER 88 C (190 F).
1 OF 3

oelheld**Material Safety Data Sheet**
acc. to ISO/DIS 11014

Page 1/4

Printing date 07/04/2008

Reviewed on 07/04/2008

1 Product and company identification

• Product details

• Product name:

IONOPLUS 3000

• Product code:

50101

• Application of the substance / the preparation

Dielectric

• Manufacturer/Supplier:

oelheld GmbH
Ulmer Str. 135-139
D-70188 Stuttgart
GERMANY
Tel.: +49-(0)711/16863-0
Fax: +49-(0)711/16863-40

E-Mail: huteo@oelheld.de
Internet: www.oelheld.de

• Information department:

Department of application: +49-(0)711/16863-71

• Emergency information:

see above or contact a Poison Control Center

2 Composition/information on ingredients

• Chemical characterization

Mixture of synthetic aliphatic hydrocarbons and active substances.

• Description:

• Dangerous components:

Synthetic aliphatic hydrocarbons

Xn, R 65-66, 50-100%

• Additional information:

For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

• Hazard description:

Not applicable.

• WHMIS classification:

The product is not subject to classification according to the Canadian WHMIS (workplace hazardous materials information system).

• Information pertaining to particular dangers for man and environment:

No hazards to be particularly mentioned. Please note the information of this Material Safety Data Sheet.

• Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

• NFPA ratings (scale 0 - 4)

Health = 0
Fire = 1
Reactivity = 0

• HMIS-ratings (scale 0 - 4)

HEALTH 0 Health = 0
FIRE 1 Fire = 1
REACTIVITY 0 Reactivity = 0

4 First-aid measures

• General information:

Remove any clothing soiled by the product.

• After inhalation:

Supply fresh air; consult doctor in case of complaints.

• After skin contact:

Wash with water and soap and rinse thoroughly.

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After ingestion:

Do not induce vomiting; immediately call for medical help.

5 Fire-fighting measures

• Suitable extinguishing media:

CO2, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.

• For safety reasons unsuitable extinguishing media:

Water with full jet

• Special hazards caused by the material, its products of combustion or resulting gases:

In certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Carbon monoxide (CO)

Sulphur dioxide (SO2)

• Protective equipment:

Wear self-contained respiratory protective device.

• Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

• Person-related safety precautions:

Ensure adequate ventilation

(Contd. on page 2)
USA

0003

Material Safety Data Sheet**1. Chemical product and company identification**

Product name CLEAREDGE 6519
MSDS # 03047
Code 03047-BE
Product use Lubricant
Manufacturer Castrol Industrial North America, Inc.
150 W. Warrenville Road
Naperville, IL 60563
Supplier Castrol Industrial North America, Inc.
150 W. Warrenville Road
Naperville, IL 60563
Product Information: 1-800-621-2661
EMERGENCY SPILL INFORMATION: 1 (800) 424-9300 CHEMTREC (USA)

2. Composition/Information on ingredients

Ingredient name	CAS #	% by weight
Distillates (petroleum), hydrotreated, heavy naphthenic (Highly refined mineral oil)	64742-52-5	25 - 30
Highly refined mineral oil (proprietary)	proprietary	1 - 5
2-Cyclohexene-1-octanoic acid, 5(OR 6)-carboxy-4-hexyl-, compd. with 2-amino-2-methyl-1-propanol	68128-58-5	1 - 5
glycine, n-methyl-n-(1-oxo-9-octadeconyl)-, (z)-, compd. with 2-amino-2-methyl-1-propanol (1:1)	68140-40-9	1 - 5
Triethanolamine	102-71-6	1 - 5
alcohols, C16-18 and C18-unsatd., ethoxylated	68920-68-1	5 - 10
3-Iodo-2-propynyl butylcarbamate	55406-53-6	0.1 - 1

3. Hazards Identification

Physical state Liquid.
Color Yellow. to Amber. (Light)
Emergency overview WARNING!
CAUSES EYE IRRITATION.
CAUSES SKIN IRRITATION.
MAY CAUSE RESPIRATORY TRACT IRRITATION.
Do not ingest. Avoid contact with skin and clothing. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.
Routes of entry Dermal contact. Eye contact. Inhalation. Ingestion.
Potential health effects
Eyes Causes eye irritation.
Skin Causes skin irritation.
Inhalation May cause respiratory tract irritation.

Product name	CLEAREDGE 6519	MSDS #	03047-BE	Page: 1/6
Version	4	Date of issue	02/01/2006.	Format US
				Language ENGLISH.
			Build 4.2.6	(ENGLISH)

MATERIAL SAFETY DATA SHEET

REVISED: 08-14-03
CURRENT AS OF: 08-14-03

GRINDKLEAN

EAGLE INTERNATIONAL, INC.
P.O. BOX 5639
STATESVILLE, NC 28687
TEL: 704-878-9583
FAX: 704-878-9585

FOR ADDITIONAL PRODUCT
INFORMATION, CALL 704-878-9583
BETWEEN 8 AM AND 5 PM EST.

SECTION #1 - IDENTIFICATION

PRODUCT NAME: **GrindKlean**

HAZARD RATING

PRODUCT USE: Metalworking grinding fluid

HEALTH: 1
FLAMMABILITY: 0
REACTIVITY: 0

SECTION #2 - HAZARDOUS COMPONENTS

COMPONENT:	CAS NO:	PERCENT:	ACGIH TLV:	OSHA PEL:
------------	---------	----------	------------	-----------

None

NOTE: OSHA requires only that hazardous components be listed in this section.

SECTION #3 - PHYSICAL DATA

APPEARANCE: Clear liquid

% VOLATILES BY VOL: 80 - 90

BOILING POINT: >212 Deg F

SOLUBILITY IN WATER: Complete

VAPOR DENSITY: >1

SPECIFIC GRAVITY: 1.01

VAPOR PRESSURE: Unknown

EVAPORATION RATE: <1 where butyl acetate=1

pH: 9.3 (neat)

ODOR: Mild

COLOR: Yellow


Safety-Kleen®

 SAFETY-KLEEN SYSTEMS, INC
 5400 LEGACY DRIVE
 PLANO, TX 75024

 DLINS NO: 05-397-8551
 FED ID NO: 30-6030019

BILL TO ADDRESS

 RIVERSIDE TOOL
 23573 COUNTY ROAD 106
 ELKHART, IN 46514-9787

SERVICE LOCATION

 RIVERSIDE TOOL
 23573 COUNTY ROAD 106
 ELKHART, IN 46514-9787

ORIGINAL INVOICE

Page 1 of 1

Account Number	Invoice Number	Invoice Date	Terms
0003053927	0036993794	07/18/08	Net 30

 SK Service Facility
 BR SOUTH BEND

 Special Billing Code #
 003 16

 Facility Phone
 574-280-4510

 Service Date
 07/17/2008

 Service Number
 0003053927

Department #	Department	Release #	Transporter	Manifest #	Tax Status/#	PO Number
00				12345		
QUANTITY	DESC./REFERENCE NUMBER		PRICE PER		SALES TAX	ITEM TOTAL
300.000	VAC SVC LIQUID REMOVAL (SAMPLED) 000006666-26-003334676-0000000 COOLANT, WATER		0.0000 GLL		0.00	0.00
1.000	FEE, FUEL SURCHARGE NON TAXABL 0000100007-00-000000000-0000000		19.1000 EA		0.00	19.10
300.000	VACUUM SERVICE WITH NO SOLIDS FEE 0000010970-00-000000000-0000000		0.9900 EA		0.00	297.00
1.000	VACUUM SERVICE FEE LEVEL 1 0000010901-00-000000000-0000000		87.0000 EA		0.00	87.00
100.000	RINSE WATER PER GALLON FOR VAC SVC 0000010921-00-000000000-0000000		0.0000 EA		0.00	0.00

SUBTOTAL	403.10
TOTAL TAX	0.00
TOTAL AMOUNT DUE	\$403.10

Comments

Please be advised delinquent payments may result in a Late Payment Charge of \$25.00. To avoid a Late Payment Charge and service interruptions, please ensure that all payments are received by the invoice due date.

The leading provider of responsible cleaning, environmental and re-refining solutions.



Please detach and enclose this coupon with your payment.


 SAFETY-KLEEN SYSTEMS, INC
 5400 LEGACY DRIVE
 PLANO, TX 75024

Account Number

0003053927

Invoice Number

0036993794

Invoice Date

07/18/08

Service Number

0003053927

 PLEASE RETURN THIS PORTION WITH PAYMENT.
 MAKE ANY ADDRESS CORRECTIONS BELOW.

Date Due

08/17/08

Amount Due

\$403.10

000369937940003053927800000403104

000454 KLEEN 1 of 2

 SAFETY-KLEEN
 PO BOX 382066

PITTSBURGH, PA 15250-8066


 RIVERSIDE TOOL
 23573 COUNTY ROAD 106
 ELKHART IN 46514